

**Packaging means for emanating pyrethroid effective in  
controlling flying insects**

Technical Field

The present invention relates generally to insect  
5 control and more particularly a packaging means for  
retaining and emanating vapour active pyrethroid that is  
effective in controlling flying insects, particularly  
mosquitoes.

Background Art

10 The control of flying insects in an indoor or an  
outdoor area has traditionally been achieved using  
articles or devices that dispense insecticide vapours into  
the atmosphere. Such articles or devices generally burn  
or heat a liquid or solid substrate to vaporise the active  
15 ingredient. For instance, in controlling mosquitoes,  
coils impregnated with an active ingredient are burnt so  
that heat from combustion causes the release of the active  
ingredient into the atmosphere, citronella oil candles are  
burnt so as to heat the citronella oil and allow it to  
20 evaporate into the atmosphere, while electric devices  
electrically heat the active ingredient so that it  
vaporises and is dispersed into the atmosphere. Battery  
operated, fan driven products are also used to control  
mosquitoes. The above mentioned products require an  
25 energy source in the form of combustion, heat or  
electricity. The release rates of active insecticides  
from continuous action products such as mosquito coils,  
candles, liquid vaporisers and electrically heated mats  
are essentially independent of the surrounding environment  
30 as the driving force for discharge of the active is  
supplied from within the system.

The abovementioned articles and devices used to control mosquitoes have disadvantages. The combustion of mosquito coils requires a safe burning site and results in ash and smoke. The burning of a candle exposes a naked  
5 flame and therefore requires a safe burning site, while the use of electricity to heat an insecticidal device is costly in some developing countries and is not portable.

There also exists ambient temperature moth repellent products that rely on passive evaporation of the  
10 insecticide from a substrate into the environment. These products, which have commonly been used to control moths, do not require an external source of energy, such as combustion, heat or electricity to release the insecticide into the atmosphere. Instead, an insecticide that  
15 vapourises at ambient temperature is required for these products. The concept of an ambient temperature moth repellent has many benefits: they provide long lasting and continuous protection; they are efficient in that there is no need for a means of heating; they are portable, modern  
20 and practical.

The above known ambient temperature products, however, also have disadvantages. Firstly, many of the prior art products are only effective in small, enclosed spaces and require significant air movement for the  
25 insecticide to be effective in a larger area of space. Secondly, there is a short falling in the number of cost-effective products that are able to work efficiently using low doses of insecticide for the control of insects other than moths, such as mosquitoes.

30 In attempting to address the above short comings, the present inventors found an effective way for controlling insects, in particular mosquitoes, using a combination of

substrate and a vapour active pyrethroid that allows passive emanation of the pyrethroid from the substrate at dose levels that achieve a minimum effective emanation rate and are cost effective. **These findings have been**  
**described previously in an application by the same**  
**applicants, the contents of which are attached as Appendix**  
**A.** Such products involving a substrate and a vapour active pyrethroid as developed by the present inventors, or indeed any of the above discussed known ambient  
10 temperature products, typically take the form of a flat substrate or a concertina-type arrangement having a number of honeycomb-like cells. The concertina-type arrangements are able to be expanded through 180° to 360° and be opened on a table to provide a bridge or fan configuration or  
15 closed into a circle to give a hanging lantern configuration or be hung to give a linear lantern configuration. There are, however, a number of disadvantages associated with such arrangements: In for instance the flat substrate arrangements, due to their  
20 flat configuration, the available surface area from which active ingredient is able to be emanated is small. As such, low rates of emanation to the atmosphere are observed. In the case of the bridge or fan configuration, the honeycomb-like cells on the extreme ends of the fan  
25 are not fully expanded thereby leading to an inefficient use of available (or potential) surface area from which active ingredients are able to emanate. As such, lower rates of emanation to the atmosphere are observed. In the case of the hanging circular or linear configurations,  
30 these require some means of attachment, such as a hook, that will allow these to be hung to a wall or ceiling. Clearly, from a consumer point of view, having to attach a

hook to a ceiling or a wall in order to allow the lantern to be hung is both time consuming and laborious and therefore undesirable. In addition, in configurations that are to be hung against the wall, reduced rates of emanation are observed due to the limited air flow around and through the substrate.

Whilst recognising the short comings of prior art articles for controlling mosquitoes and moths, the present inventors have sought to provide an improved packaging means for retaining and emanating vapour active pyrethroids that is able to achieve improved rates of emanation.

#### 15 Disclosure of the Invention

The present inventors have found that imparting verticality (or height) to the substrate results in a higher rate of emanation of the pyrethroid and therefore more efficient insect control.

20 In a first aspect, the present invention is directed a packaging means for retaining vapour active pyrethroids comprising a holder and a cellulosic based substrate or matrix impregnated and/or dosed with the vapour active pyrethroid, wherein the holder comprises a top, a base and a longitudinal member vertically extending from between the top and base, and wherein the cellulosic matrix has a honeycomb configuration adapted to be retained between the top and base and has a surface area so as to achieve sufficient emanation of the vapour active pyrethroid to control flying insects.

30 In a second aspect, the invention provides a packaging means for retaining vapour active pyrethroids

comprising a holder and a cellulosic based substrate or matrix impregnated and/or dosed with the vapour active pyrethroid, wherein the holder comprises a top, a base and a longitudinal member vertically extending from between the top and base, and wherein the cellulosic matrix has a honeycomb configuration adapted to be retained between the top and base and has a surface area so as to achieve sufficient emanation of the vapour active pyrethroid to control flying insects, and wherein the cellulosic substrate or matrix is comprised of two or more discrete parts. It has been observed that according to the second aspect of the invention, increased emanation of vapour active pyrethroid is achieved through the use of two or more discrete cellulosic substrates or matrices. Although not wishing to be bound by theory, it is believed that the increased rate of emanation is achieved by the ability of the surrounding air/atmosphere to access the regions between the one or more discrete parts. In a particularly preferred embodiment, the cellulosic substrate or matrix is comprised of two discrete parts.

The longitudinal member extending from between the holder top and base is preferably able to be releasably attached to the top and base and may be in the form of a column or a spring. When in the form of a column, preferably the column is collapsible by folding at one or more hinged joints, however the column may be comprised of one or more parts which are collapsible by telescopic movement of the one or more parts of the column within the other parts of the column. Alternatively, the column may be comprised of two or more releasably interfitting parts that are able to be interfitted by means of a slotted configuration that are able to be detached from each other

as well as the top and the base, and stored in the base. In yet a further alternative arrangement, the holder top is adapted to slide along the column thereby allowing the holder to be open and closed as required. When the  
5 longitudinal member extending from between the holder top and base is in the form of a spring, the spring may be compressed in the resting state so that the cellulosic based substrate or matrix is maintained in a collapsed state in the absence of an externally applied force.  
10 Alternatively, the spring may be uncompressed in the resting state so that the cellulosic based substrate or matrix is maintained in an extended state in the absence of an externally applied force. Preferably also, the longitudinal member is capable of being stored within the  
15 packaging means when the top and base are in a closed position.

Desirably, the holder and the cellulosic based substrate or matrix are adapted to allow the cellulosic matrix to be releasably retained in the holder and  
20 replaced as required. This may be achieved by the provision of a slot within the periphery of each of the top and base and a card on each end of the cellulosic based substrate or matrix, wherein the cards are able to be slid into the slots thereby allowing the cellulosic  
25 based substrate or matrix to be releasably attached to the holder. This configuration has the advantage of allowing the cellulosic based substrate or matrix to be replaced without the need to detach the longitudinal member from the top or base while the top and base are in the closed  
30 or open state. It is also envisaged that the cellulosic based substrate or matrix may be adapted to receive the longitudinal member through an aperture thereby retaining

the cellulosic based substrate or matrix between the top and base. In this configuration, the cellulosic based substrate or matrix is able to be replaced by detaching the top or base, or both, from the longitudinal member, 5 mounting the cellulosic based substrate or matrix about the longitudinal member, and reattaching the top or base, or both, to the longitudinal member.

In a preferred embodiment of the invention, the cellulosic based substrate or matrix is attached to the 10 top and base, wherein the base is able to be surface-mounted and is connected to the longitudinal member having a hook on its end, and wherein the cellulosic substrate or matrix is able to be extended and supported in the extended state by attachment of the top to the hook. 15 Preferably, the top is able to be attached to the hook by means of a ring located on the top.

In yet another particularly preferred embodiment of the invention, the packaging means further comprises an end-of-life (EOL) indicator. The indicator displays the 20 number of times that the product has been in use through a dial indication (counter) that rotates one increment or 'use period' by means of a toothed gearing system each time a user opens the packaging means. This indicator also displays to the user when the product is nearing end-of- 25 life.

In a third aspect, the invention provides a cellulosic based substrate or matrix having a honeycomb structure that when in an extended state, has an effective emanation surface area of about 50 - 5000 cm<sup>2</sup> and a height 30 of about 8 - 23 cm. Preferably the height is about 17.5 cm.

In a fourth aspect, the invention provides a method of emanating a vapour active pyrethroid into the atmosphere by the use of a packaging means for retaining vapour active pyrethroids comprising a holder and a  
5 cellulosic based substrate or matrix impregnated and/or dosed with the vapour active pyrethroid,

wherein the holder comprises a top, a base and a longitudinal member vertically extending from between the top and base, and

10 wherein the cellulosic based substrate or matrix has a honeycomb configuration adapted to be retained between the top and base and has a surface area so as to achieve sufficient emanation of the vapour active pyrethroid to control flying insects.

15 In a fifth aspect, the invention is directed to the use of a packaging means for retaining and emanating vapour active pyrethroids comprising a holder and a cellulosic based substrate or matrix impregnated and/or dosed with the vapour active pyrethroid,

20 wherein the holder comprises a top, a base and a longitudinal member vertically extending from between the top and base, and

wherein the cellulosic based substrate or matrix has a honeycomb configuration adapted to be retained between  
25 the top and base and has a surface area so as to achieve sufficient emanation of the vapour active pyrethroid to control flying insects.

It is desirable that the cellulosic based substrate or matrix is substantially sealed when the packaging means  
30 is in the closed state so that a minimal amount of vapour active pyrethroid is emanated into the atmosphere. This may be achieved with a protruding rim on the top and a



means for engaging the protruding rim on the base to substantially seal the vapour active pyrethroid when the top and base are in the closed state. Most preferably, the top is a lid.

5 It will be appreciated that the packaging means in accordance with the present invention may be provided to a user with or without the cellulosic based substrate or matrix. In this way, the cellulosic based substrate or matrix, in accordance with the present invention, is  
10 envisaged as a refill product that is readily able to be attached or detached as desired and replaced for example, upon depletion of the impregnated and/or dosed vapour active pyrethroid. The means of attachment may be by the use of cards (glued, stapled or otherwise attached by any  
15 conventional means known to the skilled person), to the ends of the cellulosic substrate, wherein the holder and cards are adapted so that the cards are capable of being held between the holder top and base. Alternatively, the cellulosic based substrate or matrix may be directly fixed  
20 to the top and base by means of, for example, clips, hook and loop fasteners (velcro®) or staples.

According to the various aspects of the invention, emanation of the vapour active pyrethroid from the cellulosic based substrate or matrix into the air controls  
25 flying insects. It will be understood that "control" of the flying insect population includes but is not limited to any one of or a combination of killing, repelling or knocking down a flying insect. It will be appreciated that a typical way of measuring the performance of an  
30 insecticide is in the form of "knockdown"

The phrase "surface area" is intended to mean the geometric surface area or the two dimensional surface area

of the cellulosic based substrate or matrix. For instance, in a preferred embodiment where the cellulosic based substrate or matrix is paper, the surface area is the total area of both sides of the paper. Generally, the  
5 inventors have found that an increase in the surface area, particularly the effective emanation surface area, increases the emanation rate of the vapour active pyrethroid from the cellulosic based substrate or matrix into the atmosphere. It will be understood that the  
10 effective emanation surface area is the area of the cellulosic based substrate or matrix that allows emanation of the pyrethroid into the atmosphere. For instance, the inventors have found that increasing the number of folds in a paper substrate reduces the emanation rate of the  
15 pyrethroid from the paper substrate.

The term "height" of the cellulosic based substrate or matrix is intended to mean the height of the cellulosic matrix when extended in an open position; that is, the height of the cellulosic matrix extending between the  
20 holder top and base.

The cellulosic based substrate or matrix may be any substrate or matrix that contains cellulosic fibres and includes but is not limited to ground wood pulp, chemical wood pulp, straw preferably wheat straw, bagasse (residue  
25 from crushed sugarcane), esparto grass, bamboo, flax, hemp, jute and kenaf fibres (cotton), cotton linters and recycled wastepaper in the form of, for instance, tissue, paper and cardboard. The cellulosic based substrate or matrix may be of varying grade and includes  
30 but is not limited to bleached, recycled and virgin cellulosic based substrates or matrices. It will be appreciated that different types of cellulosic based

substrates or matrices will affect the emanation rate of the vapour active pyrethroid from the substrate or matrix into the atmosphere. Preferably, the cellulosic based substrate or matrix is paper, more preferably, bleached  
5 paper.

It will be understood that a "substrate" is something which underlies or serves as a basis or foundation and a "matrix" is something which gives origin or form to a thing or which serves to enclose it. Accordingly, it will  
10 be appreciated that the term "substrate" is more applicable to flat cellulose based articles while the term "matrix" is more applicable to three-dimensional cellulose based articles.

Preferably, the cellulosic based substrate or matrix  
15 has a grammage in the range of approximately 12 gsm to 260 gsm, more preferably in the range of approximately 18 gsm to 40 gsm. Most preferably, the cellulosic based substrate or matrix has a grammage of approximately 18 gsm.

20 The cellulosic based substrate or matrix is impregnated and/or dosed with a vapour active pyrethroid. The substrate or matrix is deemed "impregnated" with the vapour active pyrethroid when the pyrethroid is either partially or completely distributed within the material of  
25 the substrate or matrix in such a manner that the pyrethroid fills all or some of the interstices of the material of the substrate or matrix and is directly held within the substrate or matrix and supported thereby. The substrate is deemed to be "dosed" with the vapour active  
30 pyrethroid when a specific quantity of the pyrethroid is applied to the substrate or matrix and absorbed either

partially or completely into the pores of the substrate or matrix.

The cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of approximately 2.0-3000 mg/m<sup>2</sup>. It will be appreciated that the amount of vapour active pyrethroid required per square metre will depend on the period of time the vapour active pyrethroid is required to emanate from the cellulose based substrate or matrix. For instance, for a cellulosic based substrate required to be effective in controlling insects, such as mosquitoes, over a 100 hour period, it is preferred that the cellulosic substrate or matrix be impregnated and/or dosed with vapour active pyrethroid in an amount of approximately 16 - 320 mg/m<sup>2</sup>, more preferably 130 - 320 mg/m<sup>2</sup>. Over a 300 hour period, it is preferred that the cellulosic substrate or matrix be impregnated and/or dosed with vapour active pyrethroid in an amount of approximately 48 - 960 mg/m<sup>2</sup>, more preferably 390 - 960 mg/m<sup>2</sup>. Over a 900 hour period, it is preferred that the cellulosic substrate or matrix be impregnated and/or dosed with vapour active pyrethroid in an amount of approximately 144 - 2880 mg/m<sup>2</sup>, more preferably, 1170 - 2880 mg/m<sup>2</sup>.

The emanation rate of the vapour active pyrethroid from the cellulosic based substrate into the atmosphere will be understood to mean the depletion of an amount of vapour active pyrethroid from the cellulosic based substrate or matrix over a certain period of time. The inventors have found that the emanation rate is affected by the surface area of the cellulose based substrate or matrix, the duration of emanation being determined by the

amount of the vapour active pyrethroid applied to the substrate or matrix.

It will be appreciated that one or more vapour active pyrethroids may be employed in the present invention. It  
5 will be understood that vapour active pyrethroids are those that are volatile at ambient temperature without heat or combustion. The volatile pyrethroids are preferably selected from the group consisting of metofluthrin, transfluthrin, empenethrin, methothrin,  
10 tefluthrin and fenfluthrin. Preferably, the vapour active pyrethroid is metofluthrin. Metofluthrin has high potency against mosquitoes, flies, and moths. The chemical name of metofluthrin is 2,3,5,6-tetrafluoro-4-(methoxymethyl)benzyl (EZ)-(1RS,3RS;1RS,3SR)-2,2-dimethyl-  
15 3-(prop-1-enyl)cyclopropanecarboxylate. Metofluthrin is available from Sumitomo Chemical Company.

Insects within the context of the invention include, but are not limited to, biting Dipterous pests (Order Diptera) such as mosquitoes (Family Culicidae), biting  
20 midges (Family Ceratopogonidae), black flies (F. Simuliidae), sandflies (certain Psychodidae) and biting flies (various families e.g. some Muscidae and Tabanidae), but may also include non-biting Dipterous insects (e.g. flies and midges of various families including Muscidae,  
25 Calliphoridae, Drosophilidae, Chironomidae and Psychodidae), as well as certain moths (Order Lepidoptera).

In the context of the present invention, the inventors have found that paper thickness and type will  
30 affect the emanation rate. Further, they have found that increasing the level of vapour active pyrethroid will increase the duration of emanation. Also increasing the

surface area, increasing the temperature and increasing the air flow will increase the emanation rate, while folding the paper will decrease the emanation rate.

The holder and the cellulosic based substrate or matrix containing the pyrethroid may be folded between an open form and a closed form such that they are expandable or are re-closable structures. This means that when insect control is not required, the holder and/or the cellulosic based substrate or matrix may be closed and stored in a form which minimises the surface area containing the vapour active pyrethroid that is exposed to the atmosphere. Conversely, when insect control is required, the holder and/or the cellulosic based substrate or matrix may be expanded into an open form thereby increasing the surface area of cellulosic based substrate or matrix containing the pyrethroid that is exposed to the atmosphere allowing the pyrethroid to emanate into the atmosphere. It is also envisaged that the amount of vapour active pyrethroid emanated into the atmosphere may be controlled by maintaining the top and base in an intermediate state between the open and closed states so that the cellulosic based substrate or matrix is in a partially expanded form.

It will be appreciated that the cellulosic based substrate or matrix is a three dimensional structure having a plurality of cells such as honeycomb like arrangements. It will also be appreciated that the cellulosic based substrate or matrix has two ends. Preferably, the two ends of the cellulosic based substrate or matrix are in contact with material through which the vapour active pyrethroid cannot migrate and/or be absorbed. Preferably, the two ends of the cellulosic

based substrate or matrix are attached to a card (for example, cardboard lined with polymer film or with aluminium foil), such that the cellulosic based substrate or matrix impregnated and/or dosed with the active  
5 pyrethroid is in contact with the polymer film or foil side of the cardboard.

The present invention will now be described in detail with reference to a number of preferred embodiments as illustrated in the accompanying drawings.

10 Brief Description of the Drawings

Figure 1 depicts a packaging means according to an embodiment of the invention wherein the top and base are in the open state within which the cellulosic based substrate or matrix is retained.

15 Figure 2a depicts an exploded view of the packaging means when in a closed state according to another embodiment of the invention wherein the longitudinal member is in the form of a column that is collapsable by disassembly about a slotted configuration. Shown is the  
20 holder top, the cellulosic cartridge, and the holder base within which the disassembled longitudinal member is stored.

Figure 2b depicts the packaging means according Figure 2a in the open state within which the cellulosic  
25 based substrate or matrix is retained.

Figure 2c depicts the packaging means according to Figure 2a in the open state without the cellulosic based substrate or matrix.

Figure 3a depicts an exploded view of the packaging  
30 means when in a closed state according to further embodiment of the invention wherein the longitudinal member is in the form of a spring. Shown is the holder

top, the cellulosic cartridge, and the holder base within which the spring is stored in a compressed state.

Figure 3b depicts the packaging means according to Figure 3a in an open state within which the cellulosic based substrate or matrix is retained.

Figure 3c depicts the packaging means according to Figure 3a in an open state without the cellulosic based substrate or matrix.

Figure 4a depicts a packaging means when in a closed state according to another embodiment of the invention wherein the longitudinal member is in the form of a column about which the tower is able to be moved along in a sliding motion wherein the column further comprises an indicator.

Figure 4b depicts the packaging means according to Figure 4a showing a cutaway view of the column and indicator mechanism.

Figure 4c depicts an exploded view of the packaging means according to Figure 4a.

Figure 4d depicts the packaging means according to Figure 4a in the open state within which the cellulosic based substrate or matrix is retained.

Figure 4e depicts the packaging means according to Figure 4a in the open state without the cellulosic based substrate or matrix.

Figure 4f depicts the packaging means according to Figure 4a in the closed state with the cellulosic based substrate or matrix, also in the closed state, ready for insertion into the holder between the top and base.

Figure 5a depicts a perspective view of the packaging means according to another embodiment of the invention wherein the base is surface-mounted and the cellulosic



matrix is attached to the base and top and is able to be retained in the extended state by means of a hook located on one end of the longitudinal member to which the top is able to be attached.

5        Figure 5b depicts a rear view of the packaging means according to Figure 5a.

Figure 5c depicts a side view of the packaging means according to Figure 5a.

Figure 6a depicts a perspective view of a packaging  
10 means in an open state according to another embodiment of the present invention wherein the cellulosic based substrate or matrix is comprised of two discrete parts.

Figure 6b depicts the packaging means of Figure 6a in a closed state.

15        Figure 6c depicts a perspective view of the cellulosic based substrate or matrix comprised of two discrete parts.

Figure 6d depicts a front view of the cellulosic based substrate or matrix according to Figure 6c.

20        Figure 6e depicts a side view of the cellulosic based substrate or matrix according to Figure 6c.

Figure 7 depicts a perspective view of a packaging means in a closed state according to another embodiment of the present invention in which the column is comprised of  
25 two interfitting parts.

#### Detailed description of the Invention

Referring to Figure 1, a packaging means according to a preferred embodiment of the invention is shown comprising a top (1), a base (3) and a cellulosic based  
30 substrate or matrix (5) retained between the top (1) and the base (3). The cellulosic based substrate or matrix (5) is a three dimensional structure with a plurality of

cells (6) such as honeycomb like shapes and a concertina type configuration having two ends which are attached to the top (1) and base (3). The cellulosic based substrate or matrix (5) may be any substrate or matrix that contains  
5 cellulose and includes but is not limited to tissue, paper, cardboard and rice paper. The cellulosic based substrate or matrix (5) may be of varying quality and includes but is not limited to bleached, recycled and virgin cellulosic based substrates or matrices. It will  
10 be appreciated that different types of cellulosic based substrates or matrices will affect the emanation rate of the vapour active pyrethroid from the substrate or matrix into the atmosphere. Preferably, the cellulosic based substrate or matrix (5) is paper, more preferably,  
15 bleached paper.

Figure 2a is directed to a packaging means according to another embodiment of the invention, this time showing detail of the longitudinal member (11) which is disassembled and stored in the base (3). Figure 2(b)  
20 shows the packaging means in an open state wherein the cellulosic based substrate or matrix (5) is retained between the top (1) and base (3). The longitudinal member (11), in this case a column that is able to be disassembled by virtue of a slotted configuration (12), is  
25 clearly shown in Figure 2(c) in the absence of the cellulosic based substrate or matrix.

A further embodiment according to the present invention is depicted in Figures 3(a) - 3(c) wherein the longitudinal member (11) is a spring. In this embodiment,  
30 the spring is expanded in the resting state and as such, the top (1) has a latch (4) which clips onto a groove (8)

in the base (3) thereby allowing the top and base to be maintained in the closed state.

A further embodiment according to the present invention is depicted in Figures 4(a) - 4(f) wherein the  
5 longitudinal member (11) is a column that is not collapsable. The top of the column comprises an indicator (20) the mechanism of which is shown in an exploded and cutaway view in Figure 4(b). In this embodiment, the top (1), by virtue of an aperture (10) (the aperture (10) is  
10 clearly depicted in Figure 4(c)), is moved towards the base (3) by sliding motion along the column (11) in order to close the holder and the attached cellulosic based substrate or matrix (5). The cellulosic based substrate or matrix (5) may be attached to the top (1) and base (3)  
15 by any conventional means known to persons skilled in the art, however, one preferred method is the use of a cards (7, 9) attached to both ends of the cellulosic matrix which may be clipped or otherwise held in position, such as by means of glue or staples. A particularly preferred  
20 method of attaching the cellulosic based substrate or matrix (5) is depicted in Figures 4(e) and 4(f) in which the top (1) and base (3) comprise slots (13) along the periphery that allows the sliding in of cards (7, 9) to thereby retain the cellulosic based substrate or matrix  
25 (5) into position. Advantageously, and as is shown in Figure 4(f), this arrangement allows the cellulosic based substrate or matrix (5) to be replaced while it, and the holder, is in the closed position.

Referring now specifically to Figure 4(b), in this  
30 particularly preferred embodiment, the EOL indicator (20) is actuated by the opening and closing of the holder. The user of the product sets a counter located at the top of

the column to the life period of the product depending on the dosage of the cellulosic based substrate or matrix with vapour active pyrethroid, for example 100 hours, by counterclockwise rotation of the counter. The counter  
5 then rotates in the clockwise direction towards zero with each opening and closing of the holder. Progress towards end-of-life is indicated, preferably by graphical means, through a window (24) located at the top of the column (11). The graphic area, visible through the window (24),  
10 is printed on a disc (21) that rotates slowly with each opening and closing of the holder. In this way, indication of EOL is able to be represented by, for example, a series of dots of changing (increasing or decreasing) size, numerical means, a change or gradation  
15 in colour or combinations of any of such representations. The upper and lower faces of the disc (21) have a mirror image saw-toothed gear profile (22) and the disc (21) is retained in a cylindrical enclosure located at the top of the column (11) with a spindle (26) providing lateral  
20 location through a hole located on a disc (25) that defines the enclosure floor, and a hole in a cap (23) that covers the cylindrical enclosure. Both the enclosure floor (disc (25)) and the underside of the cap (23) also have saw-toothed gear profiles (22a, 22b). The gears on  
25 the disc (21) can exist in one of three states: (i) engaged with the gear teeth (22b) located on disc (25), (ii) engaged with the gear teeth (22a) located on the underside of the cap (23), or (iii) in a neutral position between the gear teeth (22a, 22b) of cap (23) and disc  
30 (25) wherein this position allows the user to reset the EOL mechanism.

During operation, the holder is preferably opened at night to allow emanation of the vapour active pyrethroid when insect control is desired and closed in the morning so as to prevent emanation of the vapour active pyrethroid when insect control is not desired. As the holder is opened, a tongue (28) located on the top (1) strikes the underside of the spindle (26), driving the spindle upwards into the gear teeth (22a) on the underside of the cap (23). These gear teeth (22a) partially rotate the disc (21) in a clockwise direction as the disc gear teeth (22) and cap gear teeth (22b) engage. When the holder is next closed, the gear teeth (22) then lower back onto the gear teeth (22b) located on disc (25), again partially rotating the disc (21) clockwise. Therefore continuous opening and closing of the top translates into rotary motion of the disc (21) and in turn the rotary motion of the graphic display viewed through the window (24).

A further embodiment according to the present invention is depicted in Figures 5(a) to 5(c). In this embodiment, the packaging means comprises a cellulosic based substrate or matrix (5) that is able to be extended in the vertical direction from a base (3) to a top (1). The base (3) is able to be mounted on a surface, such as a table or ledge, and is attached at one end to the cellulosic based substrate or matrix (5) with the other end of the cellulosic substrate or matrix (5) being attached to the top (1). The top (1) is able to connected to the base (3) and the attached cellulosic based substrate or matrix supported in an open position by means of a vertically extending longitudinal member in the form of a thin rod (11) with a hook (30) at one end. When a user desires emanation of vapour active pyrethroid into

the atmosphere, the user extends the cellulosic based substrate or matrix to an open position and maintains it in the open position by hooking a ring (32) located on the top (1) on the hook (30). Conversely, when the user  
5 desires no emanation of the vapour active pyrethroid, the user allows the cellulosic based substrate or matrix (5) to retract towards the base (3) by unhooking the top (1) from the hook (30).

Another aspect of the invention is depicted in  
10 Figures 6(a) to 6(e) in which according to a preferred embodiment of this aspect, the packaging means comprises a cellulosic based substrate or matrix that is comprised of two discrete parts having substantially identical dimensions of height and width. The inventors have  
15 surprisingly found that in this configuration, an increased rate of emanation is observed. The discrete cellulosic based substrate or matrix parts may be positioned within the holder in any orientation, however, in a preferred embodiment, the parts are orientated such  
20 that the column (11) and the space (12) between the discrete parts (5a, 5b) are aligned as shown in Figure 6(a)

Referring to Figures 6(a) and 6(b), a packaging means according to the second aspect of the invention is  
25 depicted having a top (1) and a base (3) to which a two-part cellulosic based substrate or matrix (5a, 5b) is attached by means of cards (7, 9) that are able to be retained with the top (1) and base (3) by sliding motion in slots (13). The packaging means further comprises an  
30 indicator (20) which has been described in detail with reference to Figures 4(a) to 4(f). The two-part

cellulosic based substrate or matrix is also clearly depicted in Figures 6(c) to 6(e) attached to cards (7, 9).

Another preferred embodiment of the invention is depicted in Figure 7 in which the column (11) is provided to the consumer in two parts (11a, 11b) which once interfitted, are unable to be disassembled. It will be appreciated however that the present invention also provides an alternative embodiment in which the column (11) with parts (11a, 11b) is able to be releasably interfitted such that a consumer is able to assemble or disassemble the column parts (11a and 11b) as desired. In this configuration, the parts (11a, 11b) are, for example, male and female portions that are able to be releasably interfitted.

It will be appreciated by persons skilled in the art that numerous variations and/or modifications may be made to the invention as shown in the specific embodiments without departing from the spirit or scope of the invention as broadly described. The present embodiments are, therefore, to be considered in all respects as illustrative and not restrictive.

## CLAIMS:

1. A packaging means for retaining vapour active pyrethroids comprising a holder and a cellulosic based substrate or matrix impregnated and/or dosed with the  
5 vapour active pyrethroid,

wherein the holder comprises a top, a base and a longitudinal member vertically extending from between the top and base, and

wherein the cellulosic based substrate or matrix has  
10 a honeycomb configuration adapted to be retained between the top and base and has a surface area so as to achieve sufficient emanation of the vapour active pyrethroid to control flying insects.

15 2. A packaging means for retaining vapour active pyrethroids comprising a holder and a cellulosic based substrate or matrix impregnated and/or dosed with the vapour active pyrethroid, wherein the holder comprises a top, a base and a longitudinal member vertically extending  
20 from between the top and base, and wherein the cellulosic matrix has a honeycomb configuration adapted to be retained between the top and base and has a surface area so as to achieve sufficient emanation of the vapour active pyrethroid to control flying insects, and wherein the  
25 cellulosic substrate or matrix is comprised of two or more discrete parts.

3. The packaging means according to claim 2 wherein the cellulosic substrate is comprised of two parts.

30

4. The packaging means according to claim 3 wherein the two parts are of substantially identical dimensions.



5. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix has a surface area of about 50 - 5000 cm<sup>2</sup> and a height of about 8 - 23 cm.

6. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix has a surface area of about 50 - 5000 cm<sup>2</sup> and a height of about 17.5 cm.

7. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix has a surface area of about 180 - 2400 cm<sup>2</sup> and a height of about 8 - 23 cm.

8. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix has a surface area of about 180-2400 cm<sup>2</sup> and a height of about 17.5 cm.

20

9. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix has a grammage of about 12 - 260 gsm.

25 10. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix has a grammage of about 18 - 40 gsm

11. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix has a grammage of about 18 gsm.

30

12. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 2-3000 mg/m<sup>2</sup> of surface  
5 area.

13. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active  
10 pyrethroid in an amount of about 16 - 320 mg/m<sup>2</sup> of surface area.

14. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or  
15 matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 130-320 mg/m<sup>2</sup> of surface area

15. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or  
20 matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 48-960 mg/m<sup>2</sup> of surface area.

25 16. The packaging means according any one of the preceding claims wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 390-960 mg/m<sup>2</sup> of surface area.

30

17. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or

matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 144-2880 mg/m<sup>2</sup> of surface area.

5 18. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 1170-2880 mg/m<sup>2</sup> of surface area.

10

19. The packaging means according to any one of the preceding claims wherein the longitudinal member is releasably attachable to the top, base or both of the top and base.

15

20. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix, or the longitudinal vertically extending member, or both, are capable of being extended so that the top and  
20 base are in an open state or collapsed so that the top and base are in a closed state.

21. The packaging means according to claim 20 wherein the open state allows the vapour active pyrethroid to emanate  
25 into the atmosphere.

22. The packaging means according to claim 20 wherein the closed state substantially seals the cellulosic based substrate or matrix so that a minimal amount of vapour  
30 active pyrethroid is emanated into the atmosphere.

23. The packaging means according to claim 20 wherein the top and base are capable of being maintained in an intermediate state between the open and closed states thereby allowing the amount of surface area of the  
5 cellulose based substrate or matrix exposed to the atmosphere to be controlled resulting in the control of the amount of vapour active pyrethroid emanated.

24. The packaging means according to any one of the  
10 preceding claims wherein the longitudinal member vertically extending between the top and the base is a column.

25. The packaging means according to claim 24 wherein the  
15 column is collapsible by folding at one or more hinged joints.

26. The packaging means according to claim 24 or claim 25 wherein the column is comprised of one or more parts and  
20 is collapsible by telescopic movement of the one or more parts of the column within the other parts of the column.

27. The packaging means according to any one of claims 24 to 26 wherein the column is comprised of two or more  
25 interfitting parts.

28. The packaging means according to any one of claims 24 to 27 wherein the column is comprised of two or more releasable interfitting parts.

29. The packaging means according to any one of claims 24 to 27 wherein the column is comprised of two or more non-releasable interfitting parts.

5 30. The packaging means according to claim 27 wherein the parts are able to be interfitted by means of a slotted configuration wherein each respective part comprises a slot which fits into the slot of another one or more parts

10

31. The packaging means according to any one of claims 24 to 30 wherein the top is adapted to receive the column through an aperture thereby allowing the top to be moved along the column by a sliding motion so that the holder is  
15 able to be opened by sliding the top away from the base or closed by sliding the top towards the base.

32. The packaging means according to any one of the preceding claims wherein the longitudinal member  
20 vertically extending between the top and the base is a spring.

33. The packaging means according to claim 32 wherein the spring is compressed in the resting state so that the  
25 cellulosic based substrate or matrix is maintained in a collapsed state in the absence of an externally applied force.

34. The packaging means according to claim 32 or claim 33  
30 wherein the spring is uncompressed in the resting state so that the cellulosic based substrate or matrix is

maintained in an extended state in the absence of an externally applied force.

35. The packaging means according to any one of the  
5 preceding claims wherein the holder and cellulosic based substrate or matrix are adapted to allow the cellulosic matrix to be releasably retained in the holder and replaced as required.

10 36. The packaging means according to any one of the preceding claims wherein the holder comprises a slot within the periphery of each of the top and base and the cellulosic based substrate or matrix comprises a card on  
15 each of its ends, wherein the cards are able to be slid within the slots thereby allowing the cellulosic based substrate or matrix to be releasably retained in the holder.

37. The packaging means according to any one of the  
20 preceding claims wherein the cellulosic based substrate or matrix is adapted to receive the longitudinal member through an aperture thereby retaining the cellulosic based substrate or matrix between the top and base.

25 38. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix is able to be replaced by detaching the top or base, or both, from the longitudinal member, mounting the  
cellulosic based substrate or matrix about the  
30 longitudinal member, and reattaching the top or base, or both, to the longitudinal member.

39. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix is able to be removed and replaced without the need to detach either the top or base from the longitudinal  
5 member.

40. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix is able to be removed and replaced while the top  
10 and base are in a closed position.

41. The packaging means according to any one of the preceding claims wherein the longitudinal member is capable of being stored within the packaging means when  
15 the top and base are in a closed position.

42. The packaging means according to any one of the preceding claims wherein the top further comprises a protruding rim and wherein the base has a means for  
20 engaging the protruding rim to substantially seal the vapour active pyrethroid when the top and base are in the closed state.

43. The packaging means according to any one of the preceding claims wherein the top is a lid.  
25

44. The packaging means according to any one of the preceding claims further comprising an end-of-life (EOL) indicator comprising a counter, an indicator display  
30 located on the counter and a gear mechanism adapted to rotate the counter one increment each time the packaging means is extended from a closed position to an open

position and/or collapsed from an open position to a closed position, such that a user is able to ascertain from the display when the packaging means is substantially depleted in vapour active pyrethroid thereby having  
5 reached its EOL.

45. The packaging means according to claim 44 wherein the indicator display is a numeric or colour graphic display.

10 46. The packaging means according to any one of the preceding claims wherein the cellulosic based substrate or matrix is attached to the top and base, wherein the base is able to be surface mounted and is connected to the longitudinal member having a hook on its end, and wherein  
15 the cellulosic substrate or matrix is able to be extended and supported in the extended state by attachment of the top to the hook.

47. A cellulosic based substrate or matrix having a  
20 honeycomb structure that when in an extended state, has a surface area of about 50 - 5000 cm<sup>2</sup> and a height of about 8 - 23 cm.

48. The cellulosic based substrate or matrix according to  
25 claim 47 having a honeycomb structure that when in an extended state, has a surface area of about 50 - 5000 cm<sup>2</sup> and a height of about 17.5 cm.

49. A cellulosic based substrate or matrix according to  
30 claim 47 or claim 48 having a honeycomb structure that when in an extended state, has a surface area of about 180 - 2400 cm<sup>2</sup> and a height of about 8 - 23 cm.



50. The cellulosic based substrate or matrix according to any one of claims 47 to 49 having a honeycomb structure that when in an extended state, has a surface area of  
5 about 180 - 2400 cm<sup>2</sup> and a height of about 17.5 cm.

51. The cellulosic based substrate or matrix according to any one of claims 47 to 50 having a grammage of about 12 - 260 gsm.

10

52. The cellulosic based substrate or matrix according to any one of claims 47 to 51 having a grammage of about 18 - 40 gsm.

15 53. The cellulosic based substrate or matrix according to any one of claims 47 to 52 having a grammage of about 18 gsm.

54. A method of emanating a vapour active pyrethroid into  
20 the atmosphere by the use of a packaging means for retaining vapour active pyrethroids comprising a holder and a cellulosic based substrate or matrix impregnated and/or dosed with the vapour active pyrethroid,

wherein the holder comprises a top, a base and a  
25 longitudinal member vertically extending from between the top and base, and

wherein the cellulosic based substrate or matrix has a honeycomb configuration adapted to be retained between the top and base and has a surface area so as to achieve  
30 sufficient emanation of the vapour active pyrethroid to control flying insects.

55. The method according to claim 54 wherein the cellulosic based substrate or matrix has a surface area of about 50 - 5000 cm<sup>2</sup> and a height of about 8 - 23 cm.

5 56. The method according to claim 54 or 55 wherein the cellulosic based substrate or matrix has a surface area of about 50 - 5000 cm<sup>2</sup> and a height of about 17.5 cm.

57. The method according to any one of claims 54 to 56  
10 wherein the cellulosic based substrate or matrix has a surface area of about 180 - 2400 cm<sup>2</sup> and a height of about 8 - 23 cm.

58. The method according to any one of claims 54 to 57  
15 wherein the cellulosic based substrate or matrix has a surface area of about 180 - 2400 cm<sup>2</sup> and a height of about 17.5 cm.

59. The method according to any one of claims 54 to 58  
20 wherein the cellulosic based substrate or matrix has a grammage of about 12 - 260 gsm.

60. The method according to any one of claims 54 to 59  
25 wherein the cellulosic based substrate or matrix has a grammage of about 18 - 40 gsm.

61. The method according to any one of claims 54 to 60 wherein the cellulosic based substrate or matrix has a grammage of about 18 gsm.

30

62. The method according to any one of claims 54 to 61 wherein the cellulosic based substrate or matrix is

impregnated and/or dosed with vapour active pyrethroid in an amount of about 2-3000 mg/m<sup>2</sup> of surface area.

63. The method according to any one of claims 54 to 62  
5 wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 16-320 mg/m<sup>2</sup> of surface area.

64. The method according to any one of claims 54 to 63  
10 wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 130-320 mg/m<sup>2</sup> of surface area.

65. The method according to any one of claims 54 to 64  
15 wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 48-960 mg/m<sup>2</sup> of surface area.

66. The method according to any one of claims 54 to 63  
20 wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 390-960 mg/m<sup>2</sup> of surface area.

67. The method according to any one of claims 54 to 66  
25 wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 144-2880 mg/m<sup>2</sup> of surface area.

68. The method according to any one of claims 54 to 67  
30 wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 1170-2880 mg/m<sup>2</sup> of surface area.

69. The method according to any one of claims 54 to 68 for controlling any one of mosquitoes, flies, gnats, sandflies, midges, moths.

5

70. The method according to any one of claims 54 to 69 for controlling mosquitoes.

71. The use of a packaging means for retaining and  
10 emanating vapour active pyrethroids comprising a holder and a cellulosic based substrate or matrix impregnated and/or dosed with the vapour active pyrethroid,

wherein the holder comprises a top, a base and a longitudinal member vertically extending from between the  
15 top and base, and

wherein the cellulosic based substrate or matrix has a honeycomb configuration adapted to be retained between the top and base and has a surface area so as to achieve sufficient emanation of the vapour active pyrethroid to  
20 repel insects.

72. The use according to claim 71 wherein the cellulosic based substrate or matrix has a surface area of about 50 - 5000 cm<sup>2</sup> and a height of about 8 - 23 cm.

25

73. The use according to claim 71 or claim 72 wherein the cellulosic based substrate or matrix has a surface area of about 50 - 5000 cm<sup>2</sup> and a height of about 17.5 cm.

30 74. The use according to any one of claims 71 to 73 wherein the cellulosic based substrate or matrix has a

surface area of about 180 - 2400 cm<sup>2</sup> and a height of about 8 - 23 cm.

75. The use according to any one of claims 71 to 74  
5 wherein the cellulosic based substrate or matrix has a surface area of about 180 -2400 cm<sup>2</sup> and a height of about 17.5 cm.

76. The use according to any one of claims 71 to 75  
10 wherein the cellulosic based substrate or matrix has a grammage of about 12 - 260 gsm.

77. The use according to any one of claims 71 to 76  
15 wherein the cellulosic based substrate or matrix has a grammage of about 18 - 40 gsm.

78. The use according to any one of claims 71 to 77  
wherein the cellulosic based substrate or matrix has a grammage of about 18 gsm.

20

79. The use according to any one of claims 71 to 78  
wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 2-3000 mg/m<sup>2</sup> of surface area.

25

80. The use according to any one of claims 71 to 79  
wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 16-320 mg/m<sup>2</sup> of surface area.

30

81. The use according to any one of claims 71 to 80  
wherein the cellulosic based substrate or matrix is

impregnated and/or dosed with vapour active pyrethroid in an amount of about 130-320 mg/m<sup>2</sup> of surface area.

82. The use according to any one of claims 71 to 81  
5 wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 48-960 mg/m<sup>2</sup> of surface area.

83. The use according to any one of claims 71 to 82  
10 wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 390-960 mg/m<sup>2</sup> of surface area.

84. The use according to any one of claims 71 to 83  
15 wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 144-2880 mg/m<sup>2</sup> of surface area.

85. The use according to any one of claims 71 to 84  
20 wherein the cellulosic based substrate or matrix is impregnated and/or dosed with vapour active pyrethroid in an amount of about 1170-2880 mg/m<sup>2</sup> of surface area.

86. The use of the packaging means of any one of claims  
25 71 to 85 for controlling any one of mosquitoes, flies, gnats, sandflies, midges, moths.

87. The use of the packaging means of any one of claims  
71 to 86 for controlling mosquitoes.

30

88. An indicator for indicating the end-of-life (EOL) of a packaging means for retaining and emanating a vapour

active pyrethroid comprising a counter, an indicator display located on the counter and a gear mechanism adapted to rotate the counter one increment each time the packaging means is extended from closed position to an open position such that a user is able to ascertain from the display when the packaging means is substantially depleted in vapour active pyrethroid thereby having reached the EOL.

89. The indicator of claim 88 wherein the gear mechanism is adapted to rotate the counter one increment each time the packaging means is collapsed from an open position to a closed position.

90. The indicator of claim 88 or claim 89 wherein the gear mechanism is adapted to rotate the counter one increment each time the packaging means is extended from an open position to a closed position and collapsed from an open position to a closed position.

20

91. The indicator according to any one of claims 88 to 90 wherein the indication is by means of a graphic display.

92. The indicator according to claim 91 wherein the graphic display comprises a change in colour as an indicator of EOL.

91. The indicator according to claim 91 wherein the graphic display comprises a gradation in colour as an indicator of EOL.

93. The indicator according to claim 91 wherein the graphic display comprises a numerical display as an indicator of EOL.

5 94. The indicator according to claim 91 wherein the graphic display comprises a series of dots of changing size as an indicator of EOL.

95. The indicator according to any one of claims 88 to 94  
10 wherein the user is able to set the EOL indicator to a desired EOL period.

96. The indicator according to any one of claims 88 to 95 wherein the user is able to reset the EOL indicator.